

附接头固定式金属配件吸盘 /PNTK · PNYK

型号

① ② ③
 PN **T** K - **101** - **N**

①真空接口方向

②吸盘直径 mm

③吸盘橡胶材质

T	纵向接口
Y	横向接口

101	φ31	114	φ17
102	φ25	116	φ18
103	φ25	117	φ17.6
104	φ24.8	121	φ31
106	φ25	122	φ34
107	φ49	123	φ15
108	φ40	125	φ24
109	φ17	130A	φ20
110	φ23	130B	φ20
111	φ25	131	φ25
112	φ27		

N	丁腈橡胶 (101/116/122/130A/130B/131)
S	硅橡胶 (101/114/116/117/121/130A/130B/131)
U	聚氨酯橡胶 (104/110/116/125/130B)
F	氟橡胶 (130B)
NR	天然橡胶 (101/102/103/104/106/107/108/109/110/111/112/114/123)

注)上面以外的材质也可以制作,请与本公司协商。

金属配件规格

吸盘直径		107/108 以外		107/108	
真空接口方向		纵	横	纵	横
配管接头	无接头	×	×	Rc1/8	Rc1/8
	笋形接头 φ6×4	○ (M5)	○ (M5)	×	×
金属配件安装方法		公螺纹	母螺纹	公螺纹	母螺纹

吸盘标准规格

记号	材质	硬度 (Hs)	使用温度范围	颜色	体积电阻率
N	丁腈橡胶	A55/S	-26 ~ 120℃	黑色	—
S	硅橡胶	A55/S	-60 ~ 250℃	乳白色	—
U	聚氨酯橡胶	A55/S	-20 ~ 75℃	蓝色	—
NR	天然橡胶	A40/S	-60 ~ 80℃	淡茶色	—
F	氟橡胶	A70/S	-10 ~ 230℃	黑色白点	—

金属配件对应一览

	型号	圆形吸盘																				
		101	102	103	104	106	107	108	109	110	111	112	114	116	117	121	122	123	125	130A	130B	131
金属配件	纵向接口																					
	PFTK-25-K	○	○	○	○	○				○	○	○					○					
	PFTK-60-K						○	○														
金属配件	横向接口																					
	PFYK-25-K	○	○	○	○	○				○	○	○					○					
	PFYK-60-K						○	○														
止动螺纹	PFYK-15-K									○			○	○	○	○		○	○	○	○	○
	TN-PN-101-M6	○																				
	TN-PN-102-M6		○																			
	TN-PN-103-M6			○																		
	TN-PN-104-M6				○	○				○	○											
	TN-PN-107-M10						○															
	TN-PN-108-M10							○														
	TN-PN-109-M5								○													
	TN-PN-112-M6											○										
	TN-PN-114-M5												○									
	TN-PN-116-M5													○	○					○		
	TN-PF-20-M5															○						
	TN-PN-122-M6																○					
	TN-PN-123-M5																	○				
TN-PN-130-M5																			○	○	○	

注)请用止动螺纹把吸盘安装在金属配件上。